

M/V "FRIENDLY ISLANDS"

VESSEL'S PARTICULARS

SHIPS NAME :	M/V "FRIENDLY ISLANDS"						
NATIONALITY :	LIBERIA						
PORT OF REGISTRY :	MONROVIA						
CALL SIGN :	D5C16						
IMO NUMBER :	9615042						
OFFICIAL NUMBER :	15708						
CLASSIFICATION :	NIPPON KAIJI KYOKAI - N K K -					ClassNK No.:	122735
INMARSAT-C TLX No.:	463712716 (FRIE X)			MF / HF NB Telex No.:	636015708		
M.M.S.I. No.:	636015708						
E-MAIL ADDRESS :	Friendlyislands.D5C16@ipsignature3.net						
VSAT TEL No.:	+ 44 8704791823						
BUILDER :	I-S SHIPYARD Co.Ltd.,-IMABARI,EHIME ~ JAPAN						
YEAR OF BUILT :	KEEL LAID >07 May 2010 ; LAUNCHED > 03 April 2012 DELIVERED > 25th JUNE 2012						
REGISTERED OWNER :	ZODIAC MARITIME LIMITED PORTMAN HOUSE , 2 PORTMAN STREET LONDON , W1H 6DU , UK						
MANAGEMENT & ADDRESS :	TLX : 8911315 ZODAG G		UCN : -0034961				
ZODIAC MARITIME LIMITED	TEL. : +44 / 207 / 333 2222						
PORTMAN HOUSE , 2 PORTMAN STREET	FAX : +44 / 207 / 333 2233						
LONDON , W1H 6DU , UK	E - MAIL : general@zodiac-maritime.com						
P & I Club : Steamship Mutual Underwriting Association Limited, Aquatical House, 39, Bell Lane, London E1 7LU, UK							
TONNAGE	ITC '69	PC/UMS	SUEZ				
G. R. T.	17033.00	Tot vol 57699	17507.08	PANAMA CANAL ~ ACP ~ SIN.		6010014	
N. R. T.	10108.00	14252	15595.15	SUEZ CANAL		I.D. No. :	
LENGTH OVERALL	169.37 m			BREADTH MOULDED	27.20 m		
LENGTH BETWEEN PERPENDICULARS	160.40 m			DEPTH MOULDED	13.60 m		
HEIGHT FROM KEEL TO MAIN MAST TOP	40.00 m			LIGHT SHIP	6379 m/t		
FW ALLOWANCE	218 mm			TPC ("S")	39.70 m/t		
LOADLINE	Summer	Fresh	Tropical	Tropical-Fresh	Winter	MARINE SANITATION DEVICE	
FREEBOARD > m	3825.000	3607.000	3621.000	3403.000	4029.000	SEWAGE TREATMENT	
DRAFT > m	9.819	10.037	10.023	10.241	9.615	TAIKO KIKAI INDUSTRIES	
DISPLACEMENT > m/t	34766.00	34764.00	35577.00	35558.00	33959.00	TYPE: SBH-25	
DEADWEIGHT > m/t	28387.00	28385.00	29198.00	29179.00	27580.00		
CAPACITY	GRAIN		BALE		HATCHES	TANK TOPS	
	cbm	cft	cbm	cft	DIMEN. (m)	L(m)x WIDTH FWD & AFT	AREA m2
HOLD 1	5,314.00	187663.91	5,019.52	177264.35	13.60X16.00	22.20X6.40X18.80	293.40
HOLD 2	8,148.22	287754.39	7,831.74	276577.90	19.20X17.60	26.40X20.80X18.80	543.72
HOLD 3	8,199.58	289568.17	7,882.20	278359.89	19.20X17.60	26.40X20.80	549.12
HOLD 4	8,223.83	290424.56	7,882.20	278359.89	19.20X17.60	26.40X20.80	549.12
HOLD 5	7,435.00	262567.03	7,127.17	251696.01	19.20X17.60	26.40X20.80X6.40	373.44
TOTAL	37320.63	1317978.06	35742.83	1262258.04	-	-	-
STRENGTH: H/COVERS-3.3 m/t>m2 ; UPPER DCK SIDE-4,1m/t>m2;X-DCK-3,3 m/t>/m2;INNER BOTOM-15m/t>m2							
C/GEAR : 4 X CRANES, ELECT.HYDRAULIC, SINGLE HOOK TYPE-SWL 30 T, Slewing Radius-No 1, 2 & 3 = 22 m, No 4 = 24 m							
ANCHORS : 2 X BOW ANCHORS (STOCKLESS) - 4894 kg (P), 4894 kg (S) ANCHOR CHAIN=62 mm DIA x 605m (Port's & Stbd's), FLUSH BUTT WELDED STEEL, GRADE III. (11 SHACKLES P & S)							
MAIN ENGINE : MAKITA-MITSUI-MAN B&W 6S42MC Serial No. 2249							
MCR = 5850 kW / 7948 Bhp at rpm 129							
Output = 4.970 kW at 122 rpm							
PROPELLER : RIGHT HAND > 4 BLADES DIA 5250 mm, PITCH 3,653.9 mm (Mean)							
SERVICE SPEED : 14.0 knots CSO= 4970 kW / 6753 Bhp at rpm 122							
TANKS CAPACITY (100%)							
IFO = 1362 cbm	DRINKING & FW :		BALLAST				
MDO = 222 cbm	262.18 m/t		HOLD No.3, APT, FPT, DBT & TST=16049.85 cbm				

