SUBSEA SUPPORT VESSEL

Maersk Inventor

Maersk Inventor is designed together with Marin Teknikk, and is built as a flexible, stable and reliable platform to carry out a wide range of deep and shallow water operations in challenging offshore environments. With a very energy efficient propulsion set-up, this DP 3 vessel features a 400 t active heave compensated crane and 2 work class ROVs capable of operating in up to 3,000 m water depth. The large 1,850 m2 free deck is uniquely designed with hundreds of non-welding, sea fastening features, and cofferdams are built in above all tanks to ensure efficiency and flexibility for client operations. The accommodation features 120 modern single cabins to meet increased comfort level requirements.



Key features:

- 400 t AHC crane
- Dynamic Positioning Class 3
- Moonpool 8.4m x 8.4m
- 120 single cabins
- 1,850 m² deck space



Maersk Inventor

Classification		Dimensions			
	A1 Offshore Support Vessel,	Length (LOA)	137 m		
	(Supply) BWT ENVIRO+,	Beam	27.0 m		
	FFV 1 HELIDK Ice Class IC NBLES NIBS RRDA SPS	Draft scantling	8.0 m		
	CRC(I) ACCU	Deadweight	9788 t		
Dynamic positioning	DP3	Gross tonnage	14908 t		
Reference systems	2 x DGPS 232 & 5D				
	Spot track laser	Deck capacities			
	Radius 1000	Free deck area	1850 m²		
	Hipap 5012 x DGPS 232 & 5D Spot track laser	Length	83 m		
	Radius 1000	Width	26 m		
	Hipap 501				
Motion reference units	3 x Kongsberg	Propulsion			
		Generator capacity	19600 kWe		
Deck Equipment		Thrusters	2 x main propellers, 4760 BHP each		
Main Crane	Huismann - Full AHC to 3000 m water depth		3 x bow tunnels, 3740 BHP each 3 x stern tunnel, 2720 BHP		
Capacity	400 t offshore lift				
	377 t @1000 m	Accommodation			
	297 t @2000 m 217 t @3000 m		120 single cabins		
Secondary Crane	SMST - Full AHC to 3,000 m water		3 x Conference rooms 10 x Client offices		
secondary crane	depth		3 x Lounges		
Capacity	100 t offshore lift		5 X Louises		
had be been been been been been been been	93 t @1000 m	Tank capacities			
	73 t @2000 m	Drill/ballast water	7300 m ³		
	53 t @3000 m	Fresh water	1050 m ³		
Moonpool	8.4 m x 8.4 m	Fuel	2272 m ³		
Enc. Inc.		ruct	22/2 111		
FRC and lifeboats					
	1 x FRC - Seabear MKIII 2 x life boats				
	Z X tire boats				
Helideck					
	22.0 m diameter				
	12.6 t take-off weight				
DOV	CAP 437 certified				
ROV	ROV Hangar with 2 WROVs				
	1 x moon pool and 1 x over the side launched				
Pipe laying capability					
Prepared for installation of	3000 t carousel below deck				

*All figures and data believed to be correct, but not guaranteed

275 t lay tower

Engage with us

- w Maersksupplyservice.com
- Facebook.com/MaerskSupplyService
- in LinkedIn.com/company/Maersk-supply-service
- www.instagram.com/maersksupplyservice
- www.youtube.com/maersksupplyservice

Contact Information

.....

For further information on vessel specifications, capacities or vessel availability, please do not hesitate to contact the Commercial Department at chartering@maersksupplyservice.com or +45 73 73 73 73

		·	
•			